

PORTABLE VIBRATION METER **ADL M12**

The ADL M12 portable vibration meter is a simple and user-friendly diagnostic tool for monitoring vibration and solving problems related to the vibrational state of various industrial equipment.

made in
TURKEY



ADL
series

Portable vibration meter ADL M12

The ADL-M12 vibration meter will help ensure uninterrupted operation and reduce costs for repairing and servicing industrial equipment by detecting wear and damage at early stages.

The main advantages of the ADL M12 are:

- Miniature design with magnetic mounting and the possibility of attaching to an M5 stud, which eliminates the influence of the human factor on the measurement process;
- High measurement accuracy for 3 vibration parameters: vibration velocity, vibration acceleration, and vibration displacement;
- Diagnosis of rolling bearings by peak factor;
- High degree of shock and drop protection;
- Built-in battery and USB Type-C charging connector;
- Bluetooth 5.2 connectivity (option);
- Real-time data transmission to any mobile device (additional option);
- Built-in bright OLED display;
- Measurement resolution up to 0.01;
- Simplicity and ease of use.

A distinctive feature of the ADL M12 vibration meter is the ability to operate in the following modes:

Classic vibrometer – implies the use of the device as an indicator of the overall vibration level, measurement of peak values, displacement, or diagnosis of rolling bearings by peak factor. As a result, the device displays the current and averaged value. The duration of vibration value averaging can also be customized upon individual request.

This mode will be useful for daily monitoring of equipment: pumps, reducers, electric drives, and turbochargers, including both individual units of rotating equipment and the entire unit as a whole, which will provide a general understanding of the vibrational state of industrial equipment at the enterprise.

Lineman Assistant – work of the servicing personnel along a specified route with data transmission to an external device. It is possible to connect to existing software or order individual software development.

The ADL M12 vibration meter is a portable assistant for vibration control that significantly improves the vibration monitoring process, making it extremely simple, convenient, and accurate!

Specifications:

PARAMETER	VALUE		
RMS value of vibration velocity	0.01—200mm/s	Battery life depending on the intensity of work	4 - 8 h.
Peak value of vibration acceleration	0.1—200 m/s ²	Charging time, h	1,5
Peak-to-peak	2-2000 μm	Operating temperature range	-10 to +55° C
Frequency range	10-1000 Hz	Humidity, %	85
Measurement error	+/-5%	Overall dimensions (with magnetic fastening), mm	30x28x90
Protection class IP sensor	IP 54	Screen type, size, mm	OLED, 0,91"
Sensor power supply	Li-Pol battery, 3.7 V; 370 mAh		
Battery Charging Connector	USB Type-C		



TURKEY
ADELIX

Adelix Turkey

Mehmet Akif Ersoy,
Mahallesi 325. Sokak No: 3/111
06210, Yenimahalle/Ankara

+90 539 843 77 25

+90 539 843 77 25

www.adelixturkiye.com
equip@adelixturkiye.com