

# MINI DIGITAL CLAMP TESTER

AC CURRENT/LEAKAGE

Model 110

φ 30

AC  
60A

DATA  
HOLD



CE

## FEATURES

- Model 110 is a clamp-on type ammeter which is least affected by external magnetic fields.
- 30mmφCT enables the leakage current measurement for SV cable (38mm)
- Data hold function. Especially useful when working in dark or hard to get areas.
- Pocket sized and light weight.

## SPECIFICATIONS

Measuring method	: Dual integration mode
Display	: 3.5 digit LCD, max. reading of 1999
Range	: 0~2mA/20mA/60A (50/60Hz)
Ranging	: Manual ranging
Jaw opening capability	: 30mmφ
Over range indication	: Blanking of all digits except MSD1
Maximum indication	: 1999
Low battery indication	: "B" mark on LCD readout
Data hold indication	: "DH" mark on LCD readout
Sampling	: Approx. 2 times/s.
Limitation of circuit voltage	: Less than AC 600V
Operating temperature	: 0°C to 40°C, <70% RH (Non-condensing)
Storage temperature	: -10°C to 60°C, <70%RH (Non-condensing)
Power supply	: LR-44 or SR-44×2
Power consumption	: Approx. 3mW
Battery Life	: Approx. 100 hours (LR-44) Approx. 200 hours (SR-44)
Size	: 58.5(W)×158(H)×23(D)mm
Weight	: Approx. 120g
Accessories	: Batteries (LR-44) ..... 2 Instruction manual ..... 1 Carrying case ..... 1
Accuracy	: 50/60Hz

Range	Mini.Resolution	Accuracy
2mA	1μA	±1.0% rdg ±5 dgt
20mA	10μA	
60A	100mA	±1.0% rdg ±5 dgt(0~50A) ±5% rdg ±5 dgt (50A~60A)