TEMPERATURE & HUMIDITY DATA LOGGER WITH EXTERNAL PROBE



TH2020

TH2020 data loggers are ideal to monitor the temperature and humidity in transportation, storage and testing process. Recording can be started and stopped by pressing the button. User can get PDF reports by connecting the device into PC without any software or driver.

This recorder is mainly used in cold chain transportation, refrigeration, warehouse, HVAC, food & pharmaceutical of medicines, food, goods, equipments and environments that are sensitive to temperature and humidity



FEATURES

- Generate PDF report without any software and driver
- Built-in USB interface
- LCD shows recording status, readings, limit and alarm indication
- 3 mark points supported
- User configurable
- LED status and alarm indication
- · Low battery warnings
- Re-calibrate supported

TECHNICAL SPECIFICATION

| Temperature | -40~125°C (External probe: -10~65°C) |
|------------------------|--|
| Humidity | 0~100%RH (External probe: 10~90%RH) |
| Accuracy (Temperature) | ±0.3°C |
| Accuracy (Humidity) | ±3%RH |
| Resolution | 0.1°C, 0.1%RH |
| Storage Capacity | 17280 (for each channel) |
| Sample interval | 10sec to 18hours |
| Battery life | 2.5 years(25°C, 15min. interval) |
| High and low alarm | User configurable |
| Alarm delay | 0~960min |
| Alarm type | Single type; Accumulation type |
| Operation Temperature | -30~70°C |
| Storage Temperature | -30~70°C |
| Protection class | IP40 |
| Power supply | CR2032 3.0v lithium battery(factory replaceable) |
| Size | 75mm x 28mm x 10mm |
| Weight | 20 g |