

# Wöhler VIS 350 Inspection Camera



## Technical data

Monitor	Dimensions housing	176 x 114 x 32 mm	
	TFT-display	7" / 16:9 format	
	Video out	RCA signal	
	Weight	400 g	
	Power supply	Space for 2 rechargeable batteries, each 12 V or via power pack	
	Battery operating time	Max. 2 rechargeable batteries, each 120 mins. = 4 h (battery status in display)	
Wöhler pan- and tiltable camera head Ø 40, detachable	Type	1/3" COLOR CMOS	
	Pixels	768 x 576 (PAL) 656 x 492 (NTSC)	
	Light sensitivity	0,5 Lux	
	Lens	f = 2,3 mm, F = 2,5	
	Viewing angle	130°	
	Light source	12 white LEDs	
	Degree of protection	Waterproof to IP 67	
	Dimensions	Ø 40 x 60 mm	
	Operation temperature	0...40 °C, RH 95 % MAX	
	Storage temperature	-20...50 °C, RH 95 % MAX	
	Transmitter frequency	9,2 kHz	
	Wöhler miniature camera head Ø 26, detachable	Type	1/3" COLOR CMOS
		Resolution	420 lines
Pixels		768 x 576 (PAL) 656 x 492 (NTSC)	
Light sensitivity		0,5 Lux	
Lens		f = 2,3 mm, F = 2,5	
Viewing angle		145°	
Light source		12 white LEDs	
Degree of protection		Waterproof to IP 68	
Dimensions		Ø 26 x 38 mm	
Weight		240 g	
Operation temperature		0...40 °C, RH 95 % MAX	
Storage temperature		-20...50 °C, RH 95 % MAX	
Transmitter frequency		9,2 kHz	
Push rod	Length	20 m	
	Diameter	6,5 mm	
Plastic case	Dimensions	51 x 43 x 17 cm	
	Weight	8,2 kg	
Distance measurement	Electronic meter counter		
Memory (Wöhler VIS 250)	Recording	4 GB SD card (5 h recording capacity)	
	Interface	Mini USB port	

**WÖHLER**

Wöhler Technik GmbH  
Headquarters Germany

Wöhler-Platz 1 · 33181 Bad Wünnenberg

[www.woehler-international.com](http://www.woehler-international.com)