

Sound meter with one-button operation

Its small size, makes Sound Level Pen convenient for testing many sound meter applications. Auto-ranging with simple one-button operation. Press once to begin reading sound levels. Press the button a second time and the display holds the maximum reading, updating as new maximums are reached. Hold the button for 2 seconds to turn the unit off. Measures the 30 to 130 dB range in the “A” scale, with an accuracy of ± 1.5 dB. The display provides 0.1 dB resolution, under range, over range and low battery indicators. The Sound Level Pen calibrates electronically to its own internal oscillator or 2-Pt. Acoustical Calibrator (850016). Comes ready to use with 2 AAA batteries, instructions, calibration screwdriver, and a wind screen. N.I.S.T. Traceable Calibration Report available, or calibrate anytime using optional Acoustical Calibrator 850016.

DIM: 8" x 1½" x 1" (203 x 38 x 25 mm). WEIGHT: 4.3 oz (122 g).

No.	Description
840018	Sound Level Pen
840018C	Sound Level Pen Calibrated
850016	2-Pt. Acoustical Calibrator
840091	Windscreen Replacement

Range	Resolution	Accuracy
30 to 130 dB	0.1 dB	± 1.5 dB



1. On
2. Max Hold
3. Off (Press 2 Sec)



U.S. PATENT 7,270,006